

Technical Data Sheet

TL 0475-RELEASE LACQUER

“A lacquer series which is designed to provide printed surface to release from the cold seal applied surface.”

Rotogravure

R.0

PRINTING METHOD:

- Rotogravure

CHARACTERISTICS:

- Prevents the cold – seal glue on the back side of printed material rolls to stick front side.

PRINTING MATERIAL:

- OPP, PE
- Art Paper
- Metallized OPP
- Pearlized OPP

THINNING:

- IPA

PHYSICAL PROPERTIES:


- Production Viscosity: 20-25 sec (25°C / Din Cup 4)
- Printing Viscosity : 14-18 sec (25°C / Din Cup 4)
- Drying temperature : 70-80 °C
- Solid Substance : 38±2

STORAGE AND SHELF LIFE:

- For sealed buckets at room temperature, shelf life is 1 year. As the product contains some additives in it, it is useful to shake the buckets before usage after storage.



Product info published within this document are just for informational purpose and the abovementioned values have been measured in the specific conditions that are relevant to BMCOLOR’s product development, production and quality control activities. The publishing of this info doesn’t contain any guarantee or commitment related to the variable conditions of the user. BMCOLOR has the right of making changes for the products in question within the continuity of product developing.

 For further information;
+90 (212) 617 12 41